



HSF

NOTES:
 Rated Current: 1.0AMP.
 Contact Resistance: 20mΩ Max.
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min.
 Operation Temperature: -40°C to +105°C

Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA9T+33%G.F UL94V-0 BK



Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE ±0.05)



Ordering Information

1310-12 XX XX R XXX C A XX

No. of Pins Contact Plating Pin Length(Short) Insulator Packing Series No.
 Per Row: 01~50 G0=Gold Flash L=A+B+D+2.0 C=PA9T A=Tray 01-99
 G3=10u"Gold Standard: 084=8.4
 G4=15u"Gold 094=9.4
 G5=30u"Gold
 S0=Gold Flash/Tin
 S3=10u"Gold/Tin
 S4=15u"Gold/Tin
 S5=30u"Gold/Tin
 SN=Tin
 SM=Matte Tin



Item	Pin Length	A	E	B	Mating
Standard	8.4	2.40	2.20	3.00	2334
	9.4	2.40	2.20	4.00	2344
Alternate					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
				X.X	±0.40	2018/01/12	UNIT	mm [inch]	1310-12XXXXRXXXCXXX
A1	2018/01/12	MODIFY PART NO.	-----	X.XX	±0.25	DATE	SIZE	A4	TITLE:
A0	2012/03/13	NEW	-----	X.XXX	±0.15	DATE	SHEET	1/1	1.27 Pin Header, DUAL ROW, R/A, H=1.0
				Angle	± 3'	DATE	PROJ.	Customer NO.	
				DIM	TOL				

WCON
 Http: www.wcon.com
 WCON-Dongguan WCON-Kunshan
 Tel: +86 769 85358920 Tel: +86 512 57468408
 Fax: +86 769 85358915 Fax: +86 512 57468468
 E-mail: sales@wcon.com E-mail: salesks@wcon.com