



HSF

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)

NOTES:
 Rated Current: 2.0AMP.
 Contact Resistance: 20mΩ Max.
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min.
 Operation Temperature: -40°C to +105°C



Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA9T+33%G.F UL94V-0 BK



Ordering Information

1220-21 XX XX R XXX C 0 XX Δ

No. of Pins	Contact Plating	Pin Length	Insulator	Packing	Series No.
02-40	G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin	L=A+B+D1+D2+4.2 Standard:	Material C=PA9T	0=PE Bag T=Tube	01-99



TYPE 1

TYPE 2

Item	Pin Length	A	D1	B	D2
Standard	---	2.80	---	2.80	---
Alternate					

OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
X.X ±0.40	<i>Liu</i>	2018.01.19	UNIT mm		1220-21XXXXRXXXCOXX Δ
X.XX ±0.25	CHECK	DATE	SIZE A4		TITLE: PH2.00 SINGLE ROW DOUBLE PLASTIC 90° H=2.0 MIDDLE BENDING
X.XXX ±0.15	APPROVE	DATE	SHEET 1/1		Customer NO.
Angle ± 3'			PROJ.		
DIM TOL					

WCON
 Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com	WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com
---	--

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A1	2018/01/19	Modify P/N	Δ
A0	2012/04/26	NEW	-----